

Date Prepared 11/2004  
Prepared By PWatt  
Revised \_\_\_\_\_

**BMP Automotive #26**

**TITLE: Oil – Handling**

**Regulatory Citation:** 40 CFR Part 112

**Applicability:** All campus areas where 55 gallon oil drums could be handled

**Purpose:** To prevent discharges of oil to the waters of the United States during unloading and transfer of oil.

**Department Responsible:** Automotive Technician

**Schedule:** As needed

**Procedures:** Virgin and used oils are periodically handled at Hudson Valley Community College. HVCC personnel supervise / perform oil handling operations. During oil handling operations, the following procedures will be followed:

**Drum Unloading**

- Prior to unloading ensure delivery truck is secure/or and wheels are chocked;
- Check truck lift mechanism to ensure proper operation.
- Ensure spill absorbents are located in immediate vicinity and available during unloading;
- Dike or cover all drains within 50 feet of the drum unloading area prior to unloading;
- Wear proper PPE including safety glasses, steel toed shoes, and cut resistant gloves;
- Ensure container cap/drum bungs are secure prior to moving;
- Ensure hand truck is in sound mechanical condition;
- Position hand truck forks under the drum. Secure drum catch / safety strap to drum;
- Keeping the drum balanced on the hand truck, transport the drum to the oil storage area avoiding quick maneuvers;
- Position the oil drum in the appropriate storage location. Drums must be stored on spill containment pallets or in locations with suitable secondary containment; and
- Release drum catch / safety strap, and remove the hand truck.

### **Oil Handling – Transfer to Smaller containers**

- Wear proper PPE including safety glasses and cut resistant gloves;
- Ensure spill absorbents are located in immediate vicinity and available during transfer;
- Inspect transfer apparatus (i.e. mechanical hand pump, etc.) for sound mechanical condition;
- Remove container cap/drum bung and position transfer apparatus;
- Utilize and position spill catchment trays or absorbent pads at connection points to prevent spillage during transfer;
-

- Wear proper PPE including safety glasses, steel toed shoes, and cut resistant gloves;
- Ensure container cap/drum bungs are secure prior to moving;
- Ensure hand truck is in sound mechanical condition;
- Position hand truck forks under the drum. Secure drum catch / safety strap to drum;
- Keeping the drum balanced on the hand truck, transport the drum to the delivery truck avoiding quick maneuvers;
- Position the oil drum on the lift and release drum catch / safety strap, and remove the hand truck; and
- Safely position and secure drum within delivery truck.

### **Truck Loading – Vacuum Trucks**

- All drivers will stay with their vehicles during delivery;
- Prior to Shipment
  - Ensure truck is secure and wheels are chocked;
  - Ensure spill absorbents are located in immediate vicinity and available during unloading;
  - Dike or cover all drains within 50 feet of the drum unloading area prior to unloading; and
  - Check delivery hoses for evidence of deterioration or cracks.
- During Shipment
  - Carefully remove container lid to avoid residual spillage; and
  - Inspect area for leaks
- After Shipment
  - Ensure all hoses are properly disconnected and sealed;
  -