Date Prepared 11/2004
Prepared By PWatt
Revised 2/23/09 P. Watt

BMP Grounds #21

TITLE: Oil Handling

Regulatory Citation: 40 CFR Part 112

Applicability: All campus areas where 55 gallon oil drums could be handled

Purpose: To prevent discharges of oil to the waters of the United States during unloading and transfer of oil.

Department Responsible : Physical Plant Grounds Staff

Schedule: As needed

Procedures : Virgin and used oils are periodically handled at Hudson Valley Community College. HVCC personnel supervise / perform oil handling operations. During oil handling operations, the following procedures will be followed:

Drum Unloading

Prior to unloading ensure delivery truck is secure/or and wheels are choked;
Check truck lift mechanism to ensure proper operation.
Ensure spill absorbents are located in immediate vicinity and available during unloading;
Dike or cover all drains within 50 feet of the drum unloading area prior to unloading;
Wear proper PPE including safety glasses, steel toed shoes, and cut resistant gloves;
Ensure container cap/drum bungs are secure prior to moving;
Ensure hand truck is in sound mechanical condition;
Position hand truck forks under the drum. Secure drum catch / safety strap to drum;
Keeping the drum balanced on the hand truck, transport the drum to the oil storage area avoiding quick maneuvers;
Position the oil drum in the appropriate storage location. Drums must be stored on spill containment pallets or in locations with suitable secondary containment; and
Release drum catch / safety strap, and remove the hand truck.

Wear proper PPE including safety glasses, steel toed shoes, and cut resistant gloves;
Ensure container cap/drum bungs are secure prior to moving;
Ensure hand truck is in sound mechanical condition;
Position hand truck forks under the drum. Secure drum catch / safety strap to drum;
Keeping the drum balanced on the hand truck, transport the drum to the delivery truck avoiding quick maneuvers;
Position the oil drum on the lift and release drum catch / safety strap, and remove the hand truck; and
Safely position and secure drum within delivery truck.

Truck Loading – Vacuum Trucks

All drivers will stay with their vehicles during delivery;
Prior to Shipment

- Ensure truck is secure and wheels are choked;
- Ensure spill absorbents are located in immediate vicinity and available during unloading;
- Dike or cover all drains within 50 feet of the drum unloading area prior to unloading; and
- Check delivery hoses for evidence of deterioration or cracks.

During Shipment

- Carefully remove container lid to avoid residual spillage; and
- Inspect area for leaks

After Shipment

- Ensure all hoses are properly disconnected and sealed;
- Inspect area for evidence of spills;
- Ensure all valves on truck are properly closed; and
- Ensure lid to container being emptied is closed.

All spills will be immediately reported to the Director of Environmental, Health and Safety.

Record keeping: N/A
Record Location: N/A

Contact: Exec Mgr of Physical Plant (629-7427)
Assistant to the Exec Mgr (629-7361)
Grounds Supervisor (629-7565)
Director of Environmental, Health and Safety (629-7163)